

Form 1

**Type Classification Table of Products**  
**(Applicable to laminated veneer lumber, plywood, wooden flooring, medium-density fiberboard and particleboard)**

Applicant: \_\_\_\_\_ Date of Application (MM/DD/YYYY):     /     /

Contact Person: \_\_\_\_\_

Tel: \_\_\_\_\_

Address: \_\_\_\_\_

E-mail or Fax: \_\_\_\_\_

1. Type Classification

(1) C.C.C. Code: \_\_\_\_\_

(2) Chinese Name: \_\_\_\_\_

(3) English Name: \_\_\_\_\_

(4) Standard: \_\_\_\_\_

(5) Country of Production: \_\_\_\_\_

(6) Formaldehyde Emission Grade (F1, F2, or F3): \_\_\_\_\_

(7) Fire-Retardant Grade (not required for products not containing fire retardants): \_\_\_\_\_

(8) Main Type

    Thickness: \_\_\_\_\_

(9) Series Type

    Thickness: \_\_\_\_\_

2. Technical Documents Checklist (three copies of the following technical documents)

- Specification list, including the commodity structure, a cross-sectional structural diagram, and composite materials (including surface treatment materials);
- 4×6 inches color photos of the commodity (with a ruler showing the thickness of the finished product);
- Overview of manufacturing process (for commodities containing fire retardants, an overview of fire-retardant treatment process shall also be provided);
- Specimen of Chinese label;
- Samples:

- (1) Laminated veneer lumber: At least two columns shall be submitted for formaldehyde emission testing for each main type and series type. For each column, two test pieces with a surface area of 450 cm<sup>2</sup>, excluding the two cross-sectional faces, shall be taken from a portion at least 5 cm from the end along the length of the column, while maintaining the original cross-sectional dimensions.
- (2) Plywood: At least two sheets shall be submitted for formaldehyde emission testing for each main type and series type. Each sheet shall be cut into rectangular test pieces measuring 150 mm in length and 50 mm in width. The minimum number of test pieces shall be taken so that the combined area of the relevant surfaces exceeds 1800 cm<sup>2</sup>, in 2 sets. For samples containing fire retardants, three additional test pieces measuring 100 mm × 100 mm shall be submitted for fire-retardancy testing.
- (3) Wooden flooring: At least two sheets shall be submitted for formaldehyde emission testing for each main type and series type. Test pieces shall be taken from the central portion of each sheet and cut into 150 mm in length and 50 mm in width, with 10 pieces per set and 2 sets in total. For samples with particularly small specifications that cannot be cut to the foregoing dimensions, the applicant may consult the testing laboratory regarding alternative sampling arrangements.
- (4) Medium-density fiberboard and particleboard: At least two sheets shall be submitted for formaldehyde emission testing for each main type and series type. Test pieces shall be taken from each sheet so that the total surface area is approximately 1800 cm<sup>2</sup>, in 2 sets. For samples containing fire retardants, three additional test pieces measuring 100 mm × 100 mm shall be submitted for fire-retardancy testing.

Note: The specification list and commodity photos shall be arranged in the order set out in the type classification table, and the corresponding thicknesses shall be indicated.